



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

NOTES:
 Current Rating: 2.0AMP
 Contact Resistance: 20mΩ Max
 Withstand Voltage: 1000V AC/DC
 Insulation Resistance: 1000MΩ Min
 Operation Temperature: -40°C to +105°C




Contact Material: Brass
 Contact plating: Au Or Sn over Ni
 Insulator Material: LCP+30%G.F UL94V-0

Ordering Information

3221-XX R XX B S X 1

- | | | | |
|-------------|-------------------|-----------------|--------------|
| No. of Pins | Contact Plating | Insulator Color | Packing |
| 06 30 | G0=Gold Flash | B=Black | U=Blue |
| 08 34 | G3=10u"Gold | U=Blue | G=Grey(427C) |
| 10 40 | G4=15u"Gold | G=Grey(427C) | G5=30u"Gold |
| 14 44 | G5=30u"Gold | E=Grey(413C) | |
| 16 50 | S0=Gold Flash/Tin | | |
| 20 60 | S3=10u"Gold/Tin | | |
| 24 64 | S4=15u"Gold/Tin | | |
| 26 | S5=30u"Gold/Tin | | |
| | SN=Tin | | |

Item	Pitch	Mating
Standard	2.00	5225
Alternate		



REV	DATE	MODIFICATION DESCRIPTION	CHANGE	OPERATION	DRAW	DATE	SCALE	FIT	PART NO.	TITLE:	WCON-Dongguan	WCON-Kunshan
A0	2012/10/08	NEW	-----	XX	JYHuogng	2012/10/08	mm	A4	3221-XXRXXBSX1	2.0 Ejector Header" S" Type 90°	Http: www.wcon.com	
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	DIW	APPROVE	DATE	SHEET	PROJ.	Customer NO.			
							1/1					



Tel: +86 769 85358920
 Fax: +86 769 85358915
 E-mail: sales@wcon.com

Tel: +86 512 57468408
 Fax: +86 512 57468468
 E-mail: sales@wcon.com